Infra Power®

**Product** specification drawing


Basic Vertical PDU, 200~250Vac 8 outlets: UK x 8

: PD-V8UK File no.

Release date: 1 Oct 13 Version no. : V3

Safety Regulatory:

Environmental



Cordset : 3 meter 4mm sq H05V V-F cable with IEC60309 32A 2P + E plug

Input Rating 32A / 250Vac



For 32A Rating PDU, the models which have 8 socket outlets,

- < CIRCUIT A > Socket #1-4 UK socket outlets can only output 16A maximum.
- < CIRCUIT B > Socket #5-8 UK socket outlets can only output 16A maximum.

# Model: V8UK45-20A OE/3B-1



Cordset : 3 meter 2.5mm sq H05V V-F cable with 20 Amp open-end

20A / 250Vac Input Rating



20 Amp Open end

### Model: V8UK45-16A\_EN/3B-1



Cordset : 3 meter 1.5mm sq H05V V-F cable with IEC60309 16A 2P + E or IEC320 C20 plug

OR

16A / 250Vac Input Rating

#### V8UK45-16A C20/3B-1



OR



IEC 60309 16A 2P+E PLUG

16 Amp IEC320 C20

## Model: V8UK45-13A\_BS/3B-1



: 3 meter 1.5mm sq H05V V-F cable with 13 Amp BS1363 plug Cordset

: 13A / 250Vac Input Rating



13 Amp BS1363

#### Common Specification:

Description : 8 outlets UK, 45 degree (left side mounting)

Receptacles : 8 outlets UK BS1363 13A Rated, Angled 45 degree PDU Dimension : 60 (W) x 50 (D) x 650 (H) mm

Packing

Net Weight

**Gross Weight** 

UNIT: mm

WARNING: The individual user should take care to determine prior to use whether this device is suitable, adequate or safe for the use intended. Since individual applications are subject to great variation, the manufacturer makes no representation or warranty as to the suitability or fitness of these devices for any specific application.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2013 Austin Hughes Electronics Ltd. All rights reserved.



Design. Manufacturing. Global Services.