Infra Power®

**Product** specification drawing


Basic Horizontal PDU, 200~250Vac 8 outlets: UK x 8

File no. : PD-H8UK Release date: 1 Nov 13

Version no. : V2

Model: H8UK90-20A OE/3

UNIT: mm



Cordset : 3 meter 2.5mm sq H05V V-F cable with 20 Amp open-end

Input Rating 20A / 250Vac FC (E Safety Regulatory REACH Environmental

20 Amp Open end

Model: H8UK90-16A\_EN/3

OR

H8UK90-16A\_C20/3

3 meter 1.5mm sq H05V V-F cable with IEC60309 16A 2P + E or IEC320 C20 plug Cordset

Input Rating 16A / 250Vac F© (6 Safety Regulatory

Environmental REACH IEC 60309

16A 2P+E PLUG

OR



16 Amp IEC320 C20

## Model: H8UK90-13A\_BS/3



3 meter 1.5mm sq H05V V-F cable with 13 Amp BS1363 plug Cordset

Input Rating 13A / 250Vac Safety Regulatory Environmental REACH



13 Amp BS1363

Common Specification:

Description : 8 outlets UK, 90 degree

Receptacles : 8 outlets UK BS1363 13A Rated PDU Dimension : 437.5 (W) x 65 (D) x 55 (H) mm

Packing

Net Weight

**Gross Weight** 

WARNING: The individual user should take care to determine prior to use whether this device is suitable, adequate or safe for the use intended. Since individual applications are subject to great variation, the manufacturer makes no representation or warranty as to the suitability or fitness of these devices for any specific application.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2013 Austin Hughes Electronics Ltd. All rights reserved.



Design. Manufacturing. Global Services.